



TF172: TERRAFIRMA 4 STAGE ADJUSTABLE SHOCK ABSORBER – STANDARD TRAVEL - FRONT

DEFENDER 90 / 110 / 130, DISCOVERY 1 & RANGE ROVER CLASSIC

FITTING INSTRUCTIONS

- 1. Put the car into gear and apply the hand brake, loosen front wheel nuts, raise vehicle on a jack and then support the front axle on axle stands.
- 2. Remove the front wheels.
- 3. Remove the plastic cover on the inner wheel arch and expose the top of the turret.
- 4. Undo the nut on the bottom of the shock absorber remove all bushes and washers.
- 5. Undo the 4 nuts securing the shock absorber turret to the chassis bracket then Pull the turret and shock absorber out through the hole in the inner wing.
- 6. Undo the nut on the top of the shock absorber and then pull out of the turret removing all bushes and washers.
- 7. Fit the new shock absorber in through the turret, with the new washers and bushes in the correct order, then tighten the top nut.
- 8. Drop the turret and shock absorber back through the hole in the inner wing, fit the washers and nuts and tighten down the turret onto the chassis bracket.
- 9. Fit the upper bottom washers and bush, before pulling the lower part of the shock down through the spring seat. Then fit the lower bottom washers and bush and the securing nut, Tighten the bottom securing nut.
- 10. Replace the inner wing cover.
- 11. When both sides are done refit wheels lower the car off of the axle stands and torque the wheel nuts correctly.
- 12. 4-stage adjustable shocks are designed with an adjustable knob at the lower end of the body that allows you to configure your ride depending on your needs and your desired comfort. No.1 is the softest comfort setting increasing to No. 4 for the firmest sport setting.



WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sold eresponsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fittment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes/L. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications. The Terrafirma and its associated for enhancement and improvement to make sure the level of quality and performance is as expected.

TF172 90/110/130 D1/RRC