



TF221: TERRAFIRMA AIR SUSPENSION +2" LIFT ROD KIT

DISCOVERY 3, DISCOVERY 4 & RANGE ROVER SPORT

FITTING INSTRUCTIONS

1. Put the car into gear or park and apply the hand brake.
2. The height sensor rods are located behind the front and rear wheels, near the upper suspension arms. It is possible to reach them without removing the wheels. If you prefer to remove the wheels, please take all the necessary safety precautions using the correct equipment for lifting and holding the vehicle.
3. Make sure the vehicle is level or flat surface.
4. Set off-road height, engage the electric parking brake.
5. Turn off the engine and remove FUSE NUMBER #26 (20A) from the engine bay.
6. Spray the existing gromets with a penetrating lubricant and then pull the rod from the pegs which they sit on, be careful not to damage the pegs.



7. Set the desired mode for your lift rod, **SHORT SETTING - OFF-ROAD / LONG SETTING – ROAD** Secure with the blue clip. Make sure all 4 are in the same setting.



WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

**TF221
D3/D4/RRS**



8. Lubricate the grommets on the new link rods, gently push them onto the pegs. Make sure the rods are secure and fit correctly on the mounting pegs. Shorter rods being for front suspension and the longer ones being for the rear.



9. After installing all 4 of the rods, remount the wheels if you removed them previously. **Lower the vehicle down and torque the wheel nuts to the recommended torque settings – please refer to handbook**
10. Reinsert FUSE NUMBER #26 (20A). Turn on the vehicle and set the standard height.
11. Installation is now complete, For continuous use in **SHORT SETTING – OFF-ROAD** it is advisable to carry out new wheel alignment with the lift rods installed.

WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

**TF221
D3/D4/RRS**