



- 1. Put the car into gear or park and apply the hand brake.
- 2. Ensure engine and coolant is fully cooled, remove OEM/stock hoses one at a time and replace with the equivalent shaped silicone hose as you go. Care must be taken to drain and dispose of the old coolant fluids correctly.
- 3. Ensure care is taken not to damage the lining of the hose when installing the hose over the pipe ends. Do not lubricate hoses in order to fit onto pipework. If fitment is tight, use only plain cool water to help facilitate fitment.
- 4. Clamps with sold band and smooth rolled edges are recommended
- 5. Ensure the new silicone hose are fully engaged onto pipework. The clamp must be positioned at least 3mm down from the open end of the pipework and behind any bead or lip on the pipework. Ensure the hose clamp is fully seated on the hose with at least 3mm of hose protruding past the clamp.
- 6. Ensure the hoses do not rub or chaff against any part of the vehicle.
- 7. When re-filling with coolant, ensure that the vehicle manufacturer's instructions for re-filling coolant are followed.
- 8. Inspect all hoses and joints with the engine idling before the vehicle is driven. with the engine idling before the vehicle is driven.

WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to aller the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.