



TF864: TERRAFIRMA STEEL FUEL TANK GUARD

DISCOVERY 2

FITTING INSTRUCTIONS

Put the car into gear or park and apply the hand brake.

It is better to carry out this task when the fuel tank is low. It may seem like common sense but less fuel = less weight and less hassle.

Depending on the tow bar you have fitted (if at all) it may be necessary to slacken the bolts to allow the tow bar to move down facilitating easier fitting of the guard.

Support the nearside of the fuel tank with a small jack.

Undo the four mounting bolts; the two front, above the rear diff, and the two rear, next to the tow bar mounting point. Keep the rear square nuts from the chassis side of the fixing.

Remove and discard the standard tank cradle.

Using a small ratchet strap, run this under the tank using the lashing points as guides, and secure onto another part of the vehicle.

Gently lower the tank onto the strap and remove the jack.

Offer up the guard and hold it in place with the small jack (use a bit of wood or cloth to stop it scratching the main face of the guard).

Remove the strap from between the tank and guard.

Jack the guard into position and fit the guard using the four M10x30 bolts, washers and nuts (front only) as supplied.

Fully tighten all nuts and bolts to the manufacturers recommended torque settings and re-tighten tow bar as required.



WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper filtment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Lt. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Almakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

TF864