



TFWA610: TERRAFIRMA WIDE ANGLE FRONT PROPSHAFT

DEFENDER 90 / 110 / 130, DISCOVERY 1 - 1994 TO 2007 - 300TDI / V8 / TD5

FITTING INSTRUCTIONS

- 1. Park the vehicle on flat level ground, chock all four wheels front and back.
- 2. Raise one front wheel just enough to clear the ground then support the axle and vehicle on axle stands.
- 3. Undo the four nuts and bolts at the front diff end of the front propshaft. It will be easier to work round all four nuts and bolts with the vehicle out of gear, the handbrake off and one front wheel off the ground so the propshaft is free to rotate.
- 4. Undo the four nuts and bolts at the front out-put flange of the transfer box.
- 5. The propshaft may need a gently tap with a soft faced hammer, when loose remove the front propshaft.
- 6. Clean the flat surface on the transfer box and front diff flanges.
- 7. Lift the new propshaft up into place.
- 8. It is recommended to fit the new propshaft with new nyloc nuts and bolts (part numbers NZ606041L & 509045P).
- 9. Fit the new bolts through the transfer box out-put flange and then through the new propshaft fit the new nyloc's and then tighten.
- 10. Fit the new bolts through the diff flange and then through the new propshaft fit the new nyloc's and then tighten.
- 11. Grease the U.J's and the slider.
- 12. Lower the vehicle off of the axle stands.



WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the side responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper filtment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other calim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.

